

ELECTRONIC CONTROL BOARD (PWA) REPLACEMENT

IMPORTANT: BE SURE THE VALVE CAM INDICATES "SERVICE" POSITION (See Figure 1) WHEN REPLACING THE ELECTRONIC CONTROL BOARD (PWA), TO ASSURE BOTH VALVE AND PWA ARE ORIENTED, OR TIMED, TO THE SAME CYCLE. If the valve is not in Service position, see step 13 below.

NOTE: When installing the electronic control board (PWA) on the faceplate, use care not to twist the circuit board, or force it onto the mounting pegs. Twisting could damage the printed circuits, or break the display glass.

1. Unplug the water softener's transformer from electrical power
2. Remove the faceplate cover to expose the valve.
3. Unplug the wiring connections from the back of the old Electronic Control Board (See Figure 2).
4. Carefully remove the old board by unsnapping it from its retainer tabs.
5. Carefully snap the new Electronic Control Board into the retainer tabs.
6. Reconnect the wiring to the new board (See Figure 2).
7. Plug the transformer into the electrical outlet. A model code and a test number shows in the display for a few seconds.
8. If the correct model code for your softener did not display when the transformer was first plugged in, set the model code as follows: Press and hold the SELECT button until "000 - -" shows. Then press the SELECT button again until a model code (example: "E6130") shows.
9. Use the UP (+) or DOWN (-) buttons to set the correct model code for your softener (see table below). Then press the SELECT button to set, and change to the flashing "PRESENT TIME" display.

Model Number	Model Code to select
GS 6130 or EP 6130	E6130
GS 6225 or EP 6225	E6225
GS 6245 or EP 6245	E6245
GS 6260 or EP 6260	E6260
EP 6230	E6230

10. Press the UP (+) or DOWN (-) buttons to set the present time. Up moves the display ahead; down sets the time back. Be sure AM or PM is correct.
- NOTE:** Press buttons and quickly release to slowly advance the display. Hold the buttons down for fast advance.
11. Press the SELECT button a few times, until the time appears on the display, but is not flashing.
12. For information about programming additional features of the softener, consult your owner's manual.
13. If the valve is not in Service position, press the RECHARGE button and hold for 3 seconds to start a recharge cycle. The display will flash "RECHARGE NOW." In about 2 hours the recharge cycle will be complete and the valve and electronic control board will be properly oriented together.

NOTE: To save time, use the manual advance procedures to properly time and check operation. See service information in the manual.




Figure 1




Figure 2




Figure 3